



SELECTOR GUIDE

Switches and Controls

Electromechanical & Electronic Switching



Selector Guide

ELECTRONIC SWITCHING



VM-Series



CKP-Series



CKJ-Series



CM-Series

Software	SAE J1939 CAN 2.0b Protocol	SAE J1939 CAN 2.0b Protocol	SAE J1939 CAN 2.0b Protocol	SAE J1939 CAN 2.0b Protocol (Controller Module) LIN Bus (Switches)
Circuitry	3 or 6 individual rockers, up to 12 total loads	4 to 12 individual loads	5 Pushbuttons, (1) 4-directional Joystick and 1 Rotary knob	Up to 3 switches, up to 12 total loads
Actuator	12 or 24 V	8-32 V	8-32 V	9-32 VDC (Controller Module)5-32 VDC (Hardwire Switch)
Operating Voltage	Dependent or Independent LED's	1, 2, or 3 LED's per load	CAN Controlled dimmable LEDs	0, 1, 2, or 3 Independent LED's
Sealing	IP68 Front Panel; IP68 Back Panel when connected	IP69 Front Panel; IP68 Back Panel when connected	IP67 for above panel switch components	IP52 when connected
Termination	Deutsch DT-Series Connector	Deutsch DT-Series Connector	Deutsch DT-Series connector	TE connectors and terminals (see datasheet)
Legends	Custom or standard laser etched backlighting	Custom or standard laser etched backlighting	Custom or standard laser etched backlighting	Custom or standard laser etched backlighting

CONTROL



LW Wiper



LMR Mirror



LD Dimmer



V-Charger



CLTM12-S-Series

Poles	2	multi	1	1	n/a
Ratings	up to 8A 14VDC 4A 28VDC	up to 1A 14VDC .5A 28VDC	up to 10A 12VDC 5A 24VDC	up to IP65 12V/24VDC	6.5 to 32VDC
Actuator	rocker, paddle	joystick	rocker, paddle	sealed spring-loaded access doors; curved or square	n/a
Mounting Hole Specifications	.867" x 1.734" [22mm x 44mm] snap-in mount	.867" x 1.734" [22mm x 44mm] snap-in mount	.867" x 1.734" [22mm x 44mm] snap-in mount	.830" x 1.450" [21.08mm x 36.83mm] snap-in mount	3x M6 studs
Termination	.187 tabs	wire leads with connector	.250 tabs	.250 tabs	1/4" - 20 power studs
Illumination	LED	n/a	LED	LED	n/a
Sealing	n/a	n/a	IP67 above-panel	Curved Doors: IP65 above-panel when doors closed Square Doors: IP64 above-panel when doors closed	IP69k
Approvals	n/a	n/a	n/a	n/a	n/a

Selector Guide

SEALED ROCKERS



L-Series



W-Series



V-Series



HR-Charger

Poles	1, 2	1, 2	1, 2	1, 2
Ratings	IP67; up to 15A 125VAC 10A 250VAC 20A 18VDC	IP68 including connector; up to 10A 24VDC	IP66/68; up to 20/15A 12/24VDC 15A 125VAC 10A 250VAC	IP68; 20A 12V
Actuator	Rocker, Paddle, Locking Rocker	Bezel-Less Rocker, Paddle & Locking Rocker	Rocker, Paddle, Locking Rocker	Laser-Etched Rocker
Mounting Hole Specifications	.867" x 1.734" [22mm x 44mm] snap-in mount	.830" x 1.450" [21.08mm x 36.83mm] snap-in mount	.830" x 1.450" [21.08mm x 36.83mm] snap-in mount	.830" x 1.450" [21.08mm x 36.83mm] snap-in mount
Termination	.187 tab .250 tabs	.110 tabs	.250 tabs solder lug wire leads	.110 tabs
Illumination	incandescent, LED	LED	incandescent, LED, neon	LED
Sealing	n/a	n/a	UL, CSA	n/a
Approvals	n/a	n/a	n/a	n/a

FULL-SIZE ROCKERS



S-Series



TIG / LTIG / TIH / LTIH / TIL / LTIL / TII / LS

Poles	1, 2	1, 2, 3, 4
Ratings	up to 10A 28VDC	up to 15A 125VAC 10A 250VAC
Actuator	bezel-less rocker	rocker, paddle
Mounting Hole Specifications	.787" x 1.575" snap-in, keyed	.830" x 1.450" [21.08mm x 36.83mm] snap-in mount screw mount
Termination	.110 Tabs	.187 tab solder lug .250 tabs screw terms wire leads
Illumination	LED	incandescent, neon
Approvals	n/a	UL, CSA, VDE

Selector Guide

MID-SIZED ROCKERS



R / LRA / RSC / RG / LRG

RR / LRR

T / LTA / TG / LTG / TLG / TTG

Poles	1, 2	1	1, 2
Ratings	up to 20A 125VAC 15A 250VAC	up to 12A 125VAC 10A 250VAC	up to 20A 125VAC 10A 250VAC
Actuator	rocker, paddle	rocker	rocker, lever, paddle, plunger, toggle (bat)
Mounting Hole Specifications	.480" x 1.072" [12.19mm x 27.23mm] .866" x 1.182" [22mm x 30mm] snap-in mount	.795" [20.2mm] round snap-in mount	.550" x 1.125" [13.97mm x 28.57mm] 1.00" x 1.125" [25.4mm x 28.57mm] snap-in mount
Termination	solder lug .250 tabs wire leads PC terms	.187 tab	.187 tab solder lug .250 tabs wire leads
Illumination	incandescent, neon	incandescent, neon	incandescent, neon
Approvals	UL, CSA, VDE	UL, cUL	UL, CSA

SMALL-SIZED ROCKERS



651 / 652

622 / 632


611 / 621

610 / 620

Poles	1	1, 2	1, 2	1, 2
Ratings	up to 10A 125VAC 10A 250VAC 1/4 HP 125-250VAC	up to 12A 125VAC 8A 250VAC 1/2 HP 125-250VAC	up to 8A 125VAC 4A 250VAC	up to 8A 125VAC 4A 250VAC
Actuator	rocker, paddle	rocker	rocker, paddle	rocker, paddle
Mounting Hole Specifications	.508" x .756" [12.9mm x 19.2mm] snap-in mount	.508" x .756" [12.9mm x 19.2mm] snap-in mount	.508" x .756" [12.9mm x 19.2mm] snap-in mount	.508" x .756" [12.9mm x 19.2mm] snap-in mount
Termination	.187 tab solder lug wire leads PC terms	.187 tab solder lug	.187 tab solder lug wire leads PC terms	solder lug PC terms
Illumination	n/a	incandescent, LED, neon	n/a	n/a
Sealing	UL, CSA	UL, CSA	UL, CSA, VDE	UL, CSA
Approvals	n/a	n/a	n/a	n/a

Selector Guide

TOGGLES



MAAOA /
215

DK / EK

110-Series

C / D

F / G / H / I

LT-Series

ST-Series

Poles	1	1, 2	1, 2	1	1, 2, 3, 4	1, 2	1, 2
Ratings	up to 20A 125VAC 10A 250VAC 1/2HP 125- 250VAC	up to 20A 125VAC/ DC 10A 250VAC/ DC	up to 6A 125VAC/ DC 3A 250VAC/ DC	up to 20A 125VAC 10A 250VAC	up to 20A 125VAC 20A 277VAC 2 HP 250VAC	up to 15A 125VAC 10A 250VAC 15A 12-28VDC	10A 250VAC 15A 125VAC 16A 12/24VDC
Actuator	toggle (bat)	toggle (bat), toggle (ball)	toggle (bat), toggle (ball)	paddle, toggle (bat)	paddle, toggle (bat)	paddle, toggle (bat)	IP68, bat, paddle
Mounting Hole Specifications	.656" x 1.218" [16.66mm x 30.54mm] snap-in mount	.500" dia [12.7mm] bushing mount	.500" dia [12.7mm] bushing mount	.500" dia [12.7mm] bushing mount	.500" dia [12.7mm] bushing mount	.500" dia [12.7mm] bushing mount	.500" dia [12.7mm] bushing mount
Termination	.250 tabs screw terms wire leads	screw terms	solder lug .250 tabs screw terms wire leads	solder lug .250 tabs screw terms wire leads	.187 tabs solder lug .250 tabs screw terms wire leads PC terms	.187 tabs solder lug .250 tabs screw terms wire leads PC terms	.250 tabs Screw Terminals with cage clamps
Illumination	n/a	n/a	n/a	n/a	n/a	incandescent, neon	n/a
Approvals	UL, CSA	UL, CSA	UL, CSA	UL, CSA	UL, CSA, VDE	n/a	UL60079-15, cUL

PUSHBUTTONS



P / PP

641 / 110

P26 / P27

170 / 172

16-3P

AV / AVH

Poles	1	1, 2, 3	1	1	1	1
Ratings	up to 20A 125VAC 10A 250VAC	up to 5A 125VAC 2A 250VAC	up to 6A 125VAC 3A 277VAC	up to 15A 125VAC 10A 250VAC	up to 3A 125VAC	AV-Series: up to 10.1A 12VDC AVH-Series: up to 30A 12VDC
Mounting Hole Specifications	.500" dia [12.7mm] bushing mount	.500" dia [12.7mm] bushing mount	.500" dia [12.7mm] bushing mount	.500" dia [12.7mm] bushing mount	.500" dia [12.7mm] bushing mount	.748" dia [19mm] bushing mount
Termination	.250 tabs screw terms wire leads	solder lug wire leads PC terms	.250 tabs solder lug wire leads	solder lug screw terms wire leads	solder lug wire leads	.110 tabs wire leads
Approvals	UL, CSA, TUV	UL, CSA	UL, CSA	UL, CSA	UL, CSA	UL1500

Selector Guide

ROTARY



Poles	1	1	2
Ratings	up to 3A 250VAC 6A 125VAC	1.5A 250VAC 3A 125VAC 5A 12VDC	up to 15A 24VDC 20A 12VDC
Sealing / Actuator	asymmetrical	round	IP67, ergonomic knob
Mounting Hole Specifications	.500" dia [12.7mm] bushing mount	.375" dia [9.52mm] bushing mount .500" dia [12.7mm] snap-in mount	.830" x 1.450" [21.08mm x 36.83mm] snap-in mount
Termination	.125 tabs solder lug .250 tabs	wire leads	solder lug .250 tabs wire leads
Illumination	n/a	n/a	incandescent, LED
Approvals	UL, CSA	UL, CSA	pending

BATTERY DISCONNECT



	BD1-Series	BD-Series
Poles	1	1
Ratings	250 Amps 12VDC/24VDC	100-300 Amps 12VDC/24VDC
Actuator	ergonomic knob; removable option available	ergonomic knob
Mounting Hole Specifications	M6/M7 Bolt and Nut	M8 Bolt and Nut
Termination	M10 Stud; 19 and 27mm length	M10 Stud M14 Stud

COMBINATION



	CSW-Series
Poles	Multi
Ratings	10-15A 12VDC
Actuator	Pushbutton, Rotary & Lever
Mounting Hole Specifications	Round, Snap in Style
Termination	Wire Leads or Connector

Authorized Sales Representatives and Distributors

Click on a region of the map below to find your local representatives and distributors or visit www.carlingtech.com/findarep.



About Carling

Founded in 1920, Carling Technologies is a leading manufacturer of electrical and electronic switches and assemblies, circuit breakers, electronic controls, power distribution units, and multiplexed power distribution systems. With six ISO9001 and IATF16949 registered manufacturing facilities and technical sales offices worldwide, Carling Technologies Sales, Service and Engineering teams do much more than manufacture electrical components, they engineer powerful solutions! To learn more about Carling please visit www.carlingtech.com/company-profile.

To view all of Carling's environmental, quality, health & safety certifications please visit www.carlingtech.com/environmental-certifications.



European Headquarters

Carling Technologies LTD

4 Airport Business Park, Exeter Airport,
Clyst Honiton, Exeter, Devon, EX5 2UL, UK

Phone: Int + 44 1392.364422

Email: ltl.sales@carlingtech.com

Worldwide Headquarters

Carling Technologies Inc.

60 Johnson Avenue,
Plainville, CT 06062 USA

Phone: 860.793.9281

Email: sales@carlingtech.com

Asia-Pacific Headquarters

Carling Technologies, Asia-Pacific LTD.,

Suite 1607, 16/F Tower 2, The Gateway, Harbour City, 25
Canton Road, Tsimshatsui, Kowloon, Hong Kong

Phone: Int + 852-2737-2277

Email: sales@carlingtech.com.hk

WWW.CARLINGTECH.COM

